






**SERIES TAIS-MIGNON**  
**CMP\_CASS**  
**CODE 101092**



fissaggio



## Datasheet

### Electrical characteristics

Insulation Class	II
Rated insulation voltage	1000V
Rated operating voltage	-
Dissipable Power	-

### Mechanical characteristics

Manufacturing material	Palazzoli Thermosetting GRP
Treatment type	-
Surface finishing	-
Color	Grey RAL 7035
Execution	Wall mounting
Cover type	-
N. of modules on DIN rail	-
Hole type	M20
Window type	
IP Protection degree	IP65
Additional IPdegree protection	-
Shock resistance	IK04 according to IEC/EN 62262
Resistance to Glow wire	960°C
Flame rating according UL94	V-0
Corrosivity category	-
Working Environment Temp.	Min: -25°C ;Max: +70°C
Warehousing Temperature	Min: -50°C ;Max: +80°C
Dimensions	62X80X36 mm
Internal dimensions	-
Net Weight	0.104 KG

### Reference Standards and Directives

Certification and approval marks CE, UKCA, NYCE COLOMBIA

Directives 2014/35/EU (LVD)

Reference Standards EN 60670-1:2005, EN 60670-1:2005/A1:2013, EN 60670-1:2005/AC:2007, EN 60670-1:2005/AC:2010, EN 60670-22:2006

The images are purely indicative. Palazzoli reserves the right to make changes without notice.