



DIN 43650-Form A Connector

Terminal	Function
1	Supply Common
2	+V Supply
3	Command Input
4	790-2B***-Command Common
4	790-2C***-+5V Reference
4	790-2D***-Enable Input



The Embedded Electronics Amplifier is a compact, low profile coil/controller combination for use with proportional solenoid valves. The Amplifier provides current to the coil in proportion to an input signal. Bright LED indicators on the unit provide an overview of the operating status. Setup is accomplished through Sun's Amplifier Set Up Software or the Hand Held Programmer (HHP). There is no cover to remove and no tiny pots to set. Once configured, the settings are stored in permanent memory within the unit.

TECHNICAL DATA

Supply Voltage	Equals coil voltage within +/-10%
Output Current	600 mA
Dither Frequency	Off, 80-300 Hz, in 20 Hz increments
Operating Temperature Range	-4 to 158 °F
Analog Input Range	0-20 mA
Analog Input Impedance	250 ohms
Card Function	Ground Option
Voltage/Frequency	24 VDC
Connector	ISO/DIN 43650, Form A, 4-pin
Connector Environment Rating	IP65

NOTES A source type input is required. A sinking type analog input will damage the amplifier.

USED WITH

FMDA FMDB FPCC FPCH FPFK FPHK PRDL PRDM PRDN PRDP
 PSDL PSDP RBAN RBAP 991700 991702 991704