



# Un Lock

High temperature anti seize and lubricating compound

Superior lubrication under extreme pressure and extreme high temperature conditions up to 1 200°C



- Reduces friction and wear
- Assures superior thread lubrication
- Decreases risk of corrosion and seizure
- Allows disassembly without damaging gaskets

## PROBLEM SOLUTION

Bolt Corrosion	UN LOCK contains a protective anti-corrosion lubricant to protect metal parts. Has good resistance to water washout and salt spray
Damaged threads – pitting seizure and distortion	UN LOCK enables fasteners to be easily removed and reused due to its special anti seize and extreme pressure lubricants
Adhesion of gasket and metal	UN LOCK contains a heat resistant compound that prevents gasket and metal adhesion
Locked bolts from heat and age	UN LOCK uses a solid lubricating film to prevent bolts from locking

# Un Lock

High temperature anti seize and lubricating compound

ADDITIVES	BENEFITS
Refined base oil	Excellent lubricity, gives long life and low release torque
Anti oxidants	Reduces oxidation, longer service life
Metallic solid lubricant	Gives thread lubrication up to 1200°C
Corrosion inhibitors	Reduces rust & corrosion, longer thread life
Clinging additive	To keep the lubricant on the thread, leads to less wastage


TECHNICAL SPECIFICATIONS	
Colour	Silver
Aspect	Viscous paste
Specific gravity	1.045
Flash point	> 100°C


## APPLICATION AREAS


- Speedometer cables
- Exhaust pipes
- Muffler clamps
- Spark plugs
- Lug nuts
- Tyre beads
- Brake shoes
- Clutch housing
- Engine fittings and fasteners
- Head manifold gaskets

\*Consult the label for full instructions and precautions before using this product.



 NCH GmbH  
Hessenring 13  
D-64546 Mörfelden-Walldorf  
Tel.: +49 (0) 61 05 20 10  
Fax: +49 (0) 61 05 20 11 77  
E-Mail: nch\_de@nch.com

 NCH GmbH Niederl. Wien  
Rotenturmstraße 25/11  
A-1010 Wien  
Tel.: +43 (0) 1 911 30 11  
Fax: +43 (0) 1 911 30 12  
E-Mail: nch\_at@nch.com

 NCH AG / SA  
Oberneuhofstrasse 6  
CH-6340 Baar  
Tel.: +41 (0) 711 20 84/5  
Fax: +41 (0) 710 49 80  
E-Mail: nch\_ch@nch.com